

NEW! Portable Wireless 2D Bar Code Scanner

Battery-operated, wireless scanner gives you the freedom to read 2D or linear bar coded samples up to 10 meters away from the base.



- BLUETOOTH® wireless connectivity
- 33 foot (10 meters) working range
- Long lasting, rechargeable, high capacity lithium ion battery
- Reads 1D linear, PDF417, and 2D Data Matrix bar codes
- Weighs just 9 ounces
- Docking base with host-powered interface and small footprint
- Docked scanner allows hands-free bar code reading

Symbologies

2D	PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, EAN•UCC Composite
Linear	Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock
Postal	Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX
OCR Fonts	OCR-A, OCR-B

Specifications

Interfaces	Keyboard wedge, USB, TTL level RS-232, wand emulation, TTL level serial wedge, and IBM 46XX		
Frequency	2.4 to 2.4835 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v. 1.2		
Range	10 m (33 ft)	Battery	Lithium ion; 1800 mAh; 57,000 scans
Data rates	720 KBps	Hours	16 hours @ 1 scan per second
Scanner	9 oz (255 g); 6.5 in (16.5 cm) high	Charge time	4 hours for full charge at 9 VAC
Base	8.8 oz (250 g) w/o cable; 3.1 in (7.9 cm)	Input Voltage	4.2 V internal battery 4.5 to 12 VDC (host)
Temperature	Operating: 0°C to 50°C (32°F to 122°F)	Current Draw	125 mA max @ 5V (no charging)
	Storage: -20°C to 35°C (-4°F to 95°F)	Durability	Functional after 50 drops from 6 ft. (1.8 m)
Humidity	0 to 95%, non-condensing	Sealing	IP 41 (water and dust resistant)

BLUETOOTH® is a registered trademark of Bluetooth SIG, Inc. and licensed to Hand Held Products.

Catalog No.

1768-5120

Description

Wireless scanner with USB connection



MICRONIC

Traceable Sampling Solutions

Please see www.usascientific.com for more information on Micronic tubes, capping options, scanners, and tube sorters.