USA SCIENTIFIC
SIDE BY SCIENCE

LASER TOUGH-TAGS®

Labels for Microcentrifuge Tubes and Other Containers

DURABLE - Chemically inert, polyester sheets resist most organic solvents and caustic agents. They adhere to most plastics†, glass and metals without cracking, peeling or degrading.

TEMPERATURE-RESISTANT - From -40°C to 121°C, Tough-Tags resist boiling water baths, autoclaving and moderate freezer temperatures.

SPECIALLY DESIGNED - Label sheets are specially top-coated to readily accept laser printing. Heat-resistant, stay-flat sheets will not jam in laser printers.

IDEALLY SIZED - Fits a variety of microcentrifuge tubes, microscope slides and other laboratory containers. Tubes labeled with Tough-Tags will easily slide in and out of centrifuge rotors.

CLEAR - Translucent labels allow for easy viewing of tube contents.



CAT. NO.	COLOR	LABEL SIZE	LABELS PER SHT/PK	PRICE
9115-1000	Clear	1.50" x 0.75" / 38mm x 19mm	60 / 1,200	$60.00
9115-2000	Clear	1.50" x 0.50" / 38mm x 13mm	80 / 1,600	60.00
9115-3000	Clear	1.05" x 0.50" / 27mm x 13mm	96 / 1,920	60.00

ORDER INFORMATION

Online: www.usascientific.com

Phone: 1-800-522-8477
1-352-237-6288

Fax: 1-352-351-2057

Mail: USA Scientific, Inc.
PO Box 3565
Ocala, FL 34478-3565

† NOTE: Siliconized surfaces should be avoided. Apply to clean, dry tubes at room temperature. Tubes made of 100% virgin polypropylene are recommended.

See reverse side for formatting instructions in Microsoft Word® →

SCIENTIFIC
SIDE BY SCIENCE
PO Box 3565 Ocala, FL 34478-3565
Phone:1-800-522-8477 or 1-352-237-6288
Fax:1-352-351-2057 Web: www.usascientific.com

FORMATTING INSTRUCTIONS FOR

LASER TOUGH-TAGS®

IN MICROSOFT WORD®

1. Open Word
2. Click on Tools > Letters & Mailings (if you have Office XP. Office 2000 users skip to step 4.)
3. Click on Envelopes and Labels > Labels tab
4. Click on Options
5. Under Printer Information select the Laser option
6. Under Tray, select Manual Feed
7. Click on New Label to customize your label
8. Type in a name for the label (e.g. Catalog Number)
9. Insert the Label Details **[shown at bottom of page]** and click OK
10. Select the label you made in the Label Options window and click OK
11. In the Envelopes & Labels window, type your information in the area provided and click on New Document
12. When the document appears on the screen, click Edit > Select All
13. When the whole document is highlighted, choose an appropriate font and font size* and center the type using the Center command located in the toolbar

If the text in either the rows or columns do not align, continue with Steps 14 -16 otherwise skip to Step 17.

14. After centering the text, display the Tables and Borders Toolbar by clicking View > Toolbars > Tables and Borders
15. Highlight the top half of the sheet and click on the Align Center icon in the Tables and Borders Toolbar
16. Next, highlight the bottom half of the sheet and click the Align Top Center, Left or Right (depending on where the text needs to be aligned) icon in the Tables and Borders Toolbar.

17. To determine if your text will fall within the boundaries of the label, have the Gridlines showing
18. To make the gridlines appear on the screen, click on Table > Show Gridlines
19. Before printing a sheet of labels, print a test page on blank paper and line it up with a sheet of labels to ensure the text lines up correctly

Notes:
- Pass the laser sheet through the printer only once
- Manually feed the laser sheets one at a time
- Print your labels on a blank sheet of paper and check the positioning on a blank sheet of labels
- Minor adjustments may be required depending on your printer and/or software you are using

* Suggested Font Sizes: 8 pt. for smaller labels or 10-12 pt. for larger labels

Catalog No.	9115-1000	9115-2000	9115-3000
Label Size	1.50” x 0.75”	1.50” x 0.50”	1.05” x 0.50”
Top Margin	0.31”	0.56”	0.56”
Side Margin	0.25”	0.22”	0.75”
Vert. Pitch	0.88”	0.63”	0.63”
Horiz. Pitch	1.63”	1.63”	1.18”
Label Height	0.75”	0.50”	0.50”
Label Width	1.50”	1.50”	1.05”
No. Across	5	5	6
No. Down	12	16	16
Page Size	8” x 11”	8” x 11”	8” x 11”

See reverse side for more information on Tough-Tags® ⟶